


# TRIDENT Something New in RO!

It's time to boost your RO, whether it's a new build or retrofit, we have a model for you! Trident Wash Systems introduces three RO System models

# TWS RO SYSTEMS







<u>**3HP Multi-Stage Pump</u>** Stainless Steel Construction Stainless Steel Impeller Heavy Duty Motor</u>

# **Controls**

7" Graphical Touch Screen Variable Speed Pump Controller Access & Monitoring optimized to conserve water

### **Operational Information**

- City & Pump Pressures
  Pump & Reject Flow
- Reject Flow Rate
- Permeate Flow Rate
- Water Consumption (Filtered and Reject)
- TDS In & TDS Out (PPM)
- Water Temperature (F)

#### **Membranes and Housing**

- Stainless Steel Housing
- Flow Path Monitoring to optimize life of membranes
- Optimized Flow Path to reduce back pressure and increase efficiency
- LP Connections are all push to connect to simplify access for membrane replacement

#### Efficiency

- VFD controlled pressure to minimize adjustment errors and simplify set-up
- Monitoring of Permeate and Reject flow to help identify inefficiencies in water consumption
- To improve quality and efficiency, the system controls when and how often water is produced

## TRIDENT WASH SYSTEMS - DRIVEN BY EXPERIENCE, ENGINEERED FOR EXCELLENCE


# TRIDENT Something New in RO!

# The specs

Trident Wash Systems - Reverse Osmosis Systems										
Part Number	Membranes	Pump (HP)	Carbon Filter Capacity (Culn)	Feed Water (GPM)	Product Flow Rate (GPM)	Underflow Water	Dimensions			
TWS-RO-10K	4	3	2.5	9.6	6.7	2.9	24"w x 36"d x 73"t			
TWS-RO-15K	6	3	5	14.3	10	4.3	30"w x 36"d x 73"t			
TWS-RO-20K	8	3	6	12.5	9.4	3	30"w x 36"d x 73"t			


Trident Wash Systems - Carbon Filters									
Part Number	Carbon (CuFt)	Gravel (lbs)	Connections (In)	Flow Rate	Dimensions				
TWS-CF-2.5	2.5	50	1	13.5	13" x 54"				
TWS-CF-5	5	75	1 1/4	20	16" x 65"				
TWS-CF-6	6	100	1 1/2	25	21" x 62"				

### Series - Parallel Configuration



Optimizes flow paths across all membranes simultaneously to help extend lofe of membranes

## Permeate Flow Monitoring



Flow Meters monitor Permeate and Reject flow while totalizing gallons processed through Membranes

### Industrial Pump-Motor



- Stainless steel construction
- Stainless steel impellers
- 3HP High efficiency motor
- Flanged connections to hard
  plumbing

Ready for Something New in RO? Contact sales at 704-940-3707 12004 Carolina Logistics Drive, Pineville, NC 28134



## TRIDENT WASH SYSTEMS - DRIVEN BY EXPERIENCE, ENGINEERED FOR EXCELLENCE