## **RECLAIM () REIMAGINED**

Trident Wash Systems has reimagined Reclaim with two models to fit your car wash needs. Whether it's a new build or retrofit, we have a model for you!

### TWS 100

#### • 5HP Pump

• 100 GPM to Car Wash

TRIDENT

WASH SYSTEMS

- 35GPM Circulation to Tank
- Dual Stack Filters
  - Filters down to 20uM
  - Turbo Boost Flush
- Fresh Water Bypass
- Aeriation/Oxidation
  - 10gm Ozone
  - 40 L/m Air Ozone Induction
- Stainless Steel
  - Frame
  - Plumbing
  - Basket
  - Pump Impeller



#### TWS 150

- 10HP Pump
  - 150 GPM to Car Wash
  - 50GPM Circulation to Tank
- Triple Stack Filters
  - Filters down to 20uM
  - Turbo Boost Flush
- Fresh Water Bypass
- Aeriation/Oxidation
  - 10gm Ozone
  - 40 L/m Air Ozone
    Induction
- Stainless Steel
  - Frame
  - Plumbing
  - Basket
  - Pump Impeller





ANY Flow Rate



Lower Maintenance Costs



**Remote Monitoring** 

TRIDENT WASH SYSTEMS - DRIVEN BY EXPERIENCE, ENGINEERED FOR EXCELLENCE

**Key Benefits** 

# TRIDENT RECLAIM CREIMAGINED

#### **TWS 100**

TWS100 Flow Statistics								
Statistics	Reclaim Water	Circulation Water	Filtered Tank/Trench Flush Water	Underflow Water	Filter Flush Water	Fresh Water Bypass	Air Flow	
Pipe Size	2"	1 1/2"	1 1/2"	3/4"	3"*	2"	3/8"	
Flow Rate	up to 100 GPM	35 GPM	50 GPM	2-3 GPM	300 GPM*	up to 100 GPM	10 SCFM	
* Flush process moves approx 10 gallons of water in 1.5seconds. Effective flow rate during flush >300 GPM								
TWS100 Installation Information								
TWS100	Weight	Length	Depth	Height	Horse Power	Fresh Water	Air Flow	
	725	48"	3' 8"	5'6"	5	100GPM	5SCGM	

#### **TWS 150**

TWS150 Flow Statistics								
Reclaim Water	Circulation Water	Filtered Tank/Trench Flush Water	Underflow Water	Filter Flush Water	Fresh Water Bypass	Air Flow		
2"	2"	1 1/2"	1"	3"*	2"	3/8"		
up to 150 GPM	50 GPM	50 GPM	2-3 GPM	300 GPM*	up to 150 GPM	10 SCFM		
	2"	Reclaim Water 2" 2"	Reclaim WaterCirculation WaterFiltered Tank/Trench Flush Water2"2"1 1/2"	Reclaim WaterCirculation WaterFiltered Tank/Trench Flush WaterUnderflow Water2"2"1 1/2"1"	Reclaim WaterCirculation WaterFiltered Tank/Trench Flush WaterUnderflow WaterFilter Flush Water2"2"11/2"1"3"*	Reclaim WaterCirculation WaterFiltered Tank/Trench Flush WaterUnderflow WaterFilter Flush WaterFresh Water Bypass2"2"11/2"1"3"*2"		

\* Flush process moves approx 10 gallons of water in 1.5seconds. Effective flow rate during flush >300 GPM

TWS150 Installation Information								
TWS150	Weight	Length	Depth	Height	Horse Power	Fresh Water	Air Flow	
	825	58"	3'8"	5'6"	10	200GPM	5SCGM	







Ready to boost your reclaim quality? Contact sales at 704-940-3707 12004 Carolina Logistics Drive, Pineville, North Carolina 28134

TRIDENT WASH SYSTEMS - DRIVEN BY EXPERIENCE, ENGINEERED FOR EXCELLENCE